

MAX. VOC 150 g/L

This product meets SCAQMD Rule 1113-Architectural Coatings; Metallic Pigmented Coatings

Modern Masters Inc.  
Valencia, CA 91355 USA  
(800) 942-3166

[modernmasters.com](http://modernmasters.com)

© 2015, Modern Masters Inc.  
Made in USA

CONFORMS TO ASTM D4236

ME39616



MM200084 1015

**Metal Effects®** water base **Oxidizing Bronze Paint** contains real copper and zinc particles that will oxidize when **Metal Effects Patina Aging Solutions** either **Blue** or **Green** are used over **Oxidizing Bronze Paint** creating authentic blue or green patinaed metal finishes.

**SURFACE PREPARATION:** Apply two coats of **Metal Effects Primer** per the instructions on the label and allow to cure.

**APPLICATION:** Apply first coat of **Oxidizing Bronze Paint** with a brush, roller, or HVLP spray gun with compressor and let dry. Apply second coat in the same manner and while paint film is still wet, apply **Blue** or **Green Patina Aging Solution** onto the wet paint film using a sea sponge, brush, or spray by attaching the **Spritzer Cap**.

**PROTECTION:** Patina finishes do not require a clear protective finish, but if desired, use **Metal Effects Permacoat Xtreme** per instructions on the container.

**WARRANTY:** This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used if such product proves defective within two years of manufacture. No other warranty is expressed or implied.



# METAL EFFECTS® OXIDIZING BRONZE PAINT

Water Base 16 fl. oz. / 473 ml Low VOC

**COVERAGE:** Covers approx. 40 sq. ft./16oz., 3.7 m<sup>2</sup>/473 ml.

**DRY TIME:** Recoat time is approx. 1/2 hour. Dry time is approx. 1 hour. The dry time will vary with temperature and humidity.

**CLEAN UP:** Clean brushes, rollers, tools, and equipment with warm, soapy water immediately after use.

**HANDLING & STORAGE:** Close container after each use. Protect from freezing. If contents freeze, allow to thaw at room temperature before use. **Stir thoroughly before use.** Do not apply at temperatures below 55°F/13°C. Dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**HEALTH & SAFETY:** Avoid contact with eyes. Wash hands after use. Do not take internally. When spraying or sanding wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for use.

**KEEP OUT OF REACH OF CHILDREN**