

Metallic Paint Collection™

Cool Tone Primer

Ideal Primer and Foundation Color for Metallic Paint Collection

For Use Under Cool Colors

Gray

Interior | Exterior

1 US Gal. | 3.78 L

Water-Base

Tintable

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-942-3166 for product replacement or a full refund of the purchase price. Refer to product number and batch code.



11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-942-3166 modernmasters.com
Made in USA | Hecho en E.U.A.
©2018 Rust-Oleum Corporation 340498 0418

337184 COOL TONE PRIMER



0 20066 42312 4

COVERAGE COBERTURA 350-450 sq ft / gal pies cuadrados / gal
Depends on application and surface <i>Depende de la aplicación y de superficie</i>

Drying Time <i>Tiempo de Secado</i> @ 50% RH	50°-90°F Touch: 30 min. <i>Tacto: 30 minutos</i>
	Sandable: 1-2 hours <i>Se puede lijar: 1-2 horas</i>
Temperature and humidity dependent <i>Dependiente de temperatura y humedad</i>	Recoat: 1-2 hours <i>Repintar: 1-2 horas</i>

Metallic Paint Primer is an ideal primer and foundation color for Modern Masters' Metallic Paint Collection, Matte Metallics and Exterior Metallic Paints. It promotes adhesion on smooth surfaces, dries fast and is immediately sandable when dry. It also provides excellent stain-blocking power and tolerates pH levels up to 13. Use Cool Tone Primer under Silver and Pewter Metallic colors. For Gold and Copper Metallic colors, use Modern Masters Warm Tone Primer.

WHERE TO USE: Metallic Paint Primer is suitable for concrete, masonry, non-ferrous metal, galvanized steel, plastic, wallboard, wood, plaster, stucco, and previously coated surfaces. It can be used for both interior and exterior applications.

SURFACE PREPARATION: ALL SURFACES: Remove dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. If any mold or mildew is present on the surface clean further with one quart of household bleach added to a gallon of water. Rinse with clean water. Severely mildewed areas should be cleaned with a chlorinated cleansing powder and thoroughly rinsed with water. All surfaces must be dry at time of application. **GALVANIZED STEEL:** New galvanized steel should be solvent cleansed to remove all post galvanizing treatments such as oil, grease or wax. Old or existing galvanized steel should be thoroughly washed to remove all surface contaminants. **CONCRETE AND MASONRY:** Hand or power tool clean to remove all loose or unsound concrete, masonry, or previous coating. Very dense, non-porous, concrete should be acid etched

or abrasive blasted to remove the laitance layer and create a surface profile. Allow new concrete to cure for 30 days before coating. **PREVIOUSLY COATED:** Previously coated surfaces must be sound and in good condition. Smooth, hard or glossy finishes should be scarified by sanding to create a surface profile. **APPLICATION METHODS:** Mix thoroughly. Product is formulated to be used as is. Apply only when air and surface temperatures are between 50°-90°F (10°-32°C), the relative humidity is no greater than 85%, and surface is at least 5°F (3°C) above dew point. Dry times may be effected by extremely high or low relative humidity. Ensure fresh air entry during application and when drying. **Brushing:** Use a high-quality synthetic bristle brush. **Rolling:** Use a high-quality low nap roller. **Spraying:** Air - Atomized Spray (pressure feed only): Fluid tip - 0.055-.0.070; Fluid Delivery - 10-16 oz/min; Atomizing Pressure - 25-60 psi. Airless Spray: Fluid Pressure - 1800-3000psi; Fluid Tip - 0.013-0.017; Filter Mesh - 100.

TINTING: To improve hide and coverage with darker and deeper colors, Cool Tone primer can be tinted to even darker tones with up to 2 oz. of universal colorant per gallon. Tinting may increase dry times. **HANDLING & STORAGE:** To avoid skinning, close container tightly after each use and store product in room temperature. Dispose of unused or unwanted product in accordance with local laws regulating water base coatings. **CLEAN UP:** Clean brushes, rollers, tools and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth. **HEALTH & SAFETY:** Use in a well ventilated area. Avoid contact with eyes. Wash hands

thoroughly with soap and warm water after use. Do not take internally. When spraying or sanding, use a properly fitting (NIOSH approved) respirator per the manufacturer's instructions. **Skin contact:** Thoroughly wash with soap and warm water before the coating dries. Individuals with sensitive skin may require gloves. **Eye contact:** Rinse with clean water for 15 minutes. Seek medical attention. **Inhalation:** To help prevent irritation, use only in well-ventilated areas. If irritation occurs, move to fresh air. If irritation persists, seek medical attention. **Ingestion:** Do not induce vomiting. Seek medical attention.

Read the Safety Data Sheet for Additional Health and Safety Information.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

KEEP OUT OF REACH OF CHILDREN

WARRANTY: This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit modernmasters.com for Technical Data Sheets, Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.

VOC: <100 g/L



Metallic Paint Collection™

Warm Tone Primer

Ideal Primer and Foundation Color for
Metallic Paint Collection

For Use Under Warm Colors



Beige

Interior | Exterior

1 US Gal. | 3.78 L

Water-Base

Tintable



SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-942-3166 for product replacement or a full refund of the purchase price. Refer to product number and batch code.



11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-942-3166 modernmasters.com
Made in USA | Hecho en E.U.A.
©2018 Rust-Oleum Corporation 340499 0418

337185 WARM TONE PRIMER



0 20066 42311 7

COVERAGE COBERTURA 350-450 sq ft / gal pies cuadrados / gal
Depends on application and surface <i>Depende de la aplicación y de superficie</i>

Drying Time <i>Tiempo de Secado</i> @ 50% RH	50°-90°F Touch: 30 min. <i>Tacto: 30 minutos</i>
	Sandable: 1-2 hours <i>Se puede lijar: 1-2 horas</i>
Temperature and humidity dependent <i>Dependiente de temperatura y humedad</i>	Recoat: 1-2 hours <i>Repintar: 1-2 horas</i>

Metallic Paint Primer is an ideal primer and foundation color for Modern Masters' Metallic Paint Collection, Matte Metallics and Exterior Metallic Paints. It promotes adhesion on smooth surfaces, dries fast and is immediately sandable when dry. It also provides excellent stain-blocking power and tolerates pH levels up to 13. Use Warm Tone Primer under Gold and Copper Metallic colors. For Silver and Pewter Metallic colors, use Modern Masters Cool Tone Primer.

WHERE TO USE: Metallic Paint Primer is suitable for concrete, masonry, non-ferrous metal, galvanized steel, plastic, wallboard, wood, plaster, stucco, and previously coated surfaces. It can be used for both interior and exterior applications.

SURFACE PREPARATION: ALL SURFACES: Remove dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. If any mold or mildew is present on the surface clean further with one quart of household bleach added to a gallon of water. Rinse with clean water. Severely mildewed areas should be cleaned with a chlorinated cleansing powder and thoroughly rinsed with water. All surfaces must be dry at time of application. **GALVANIZED STEEL:** New galvanized steel should be solvent cleansed to remove all post galvanizing treatments such as oil, grease or wax. Old or existing galvanized steel should be thoroughly washed to remove all surface contaminants. **CONCRETE AND MASONRY:** Hand or power tool clean to remove all loose or unsound concrete, masonry, or previous coating. Very dense, non-porous, concrete should be acid etched

or abrasive blasted to remove the laitance layer and create a surface profile. Allow new concrete to cure for 30 days before coating. **PREVIOUSLY COATED:** Previously coated surfaces must be sound and in good condition. Smooth, hard or glossy finishes should be scarified by sanding to create a surface profile. **APPLICATION METHODS:** Mix thoroughly. Product is formulated to be used as is. Apply only when air and surface temperatures are between 50°-90°F (10°-32°C), the relative humidity is no greater than 85%, and surface is at least 5°F (3°C) above dew point. Dry times may be effected by extremely high or low relative humidity. Ensure fresh air entry during application and when drying. **Brushing:** Use a high-quality synthetic bristle brush. **Rolling:** Use a high-quality low nap roller. **Spraying:** Air - Atomized Spray (pressure feed only): Fluid tip - 0.055-.0.070; Fluid Delivery - 10-16 oz/min; Atomizing Pressure - 25-60 psi. Airless Spray: Fluid Pressure - 1800-3000psi; Fluid Tip - 0.013-0.017; Filter Mesh - 100.

TINTING: To improve hide and coverage with darker and deeper colors, Warm Tone primer can be tinted to even darker tones with up to 2 oz. of universal colorant per gallon. Tinting may increase dry times.

HANDLING & STORAGE: To avoid skinning, close container tightly after each use and store product in room temperature. Dispose of unused or unwanted product in accordance with local laws regulating water base coatings. **CLEAN UP:** Clean brushes, rollers, tools and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

HEALTH & SAFETY: Use in a well ventilated area. Avoid contact with eyes. Wash hands

thoroughly with soap and warm water after use. Do not take internally. When spraying or sanding, use a properly fitting (NIOSH approved) respirator per the manufacturer's instructions. **Skin contact:** Thoroughly wash with soap and warm water before the coating dries. Individuals with sensitive skin may require gloves. **Eye contact:** Rinse with clean water for 15 minutes. Seek medical attention. **Inhalation:** To help prevent irritation, use only in well-ventilated areas. If irritation occurs, move to fresh air. If irritation persists, seek medical attention. **Ingestion:** Do not induce vomiting. Seek medical attention.

Read the Safety Data Sheet for Additional Health and Safety Information.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

KEEP OUT OF REACH OF CHILDREN

WARRANTY: This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit modernmasters.com for Technical Data Sheets, Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.

VOC: <100 g/L

340499 0418