



colorfast^{non-fading™}
EX ZERO VOC
acrylic polyurethane
activator (component B)

industrial use only
by professional, trained painters.
not intended for sale to or use by general public.

ACTIVATOR

1 US QUART / 946 ml

IMPORTANT: The contents of this package must be blended with components before the product can be used. Before opening the packages read all warning labels, SDS and TDS information. It is recommended to review applicable state and local regulations before using product. Follow all precautions recommended for use of this product.

MIXING AND THINNING INSTRUCTIONS: This is a two-component paint system. First, mix each component thoroughly. Open the Activator (component B) carefully. Do not open if container is bulged. Discard if container is bulged or product is not clear. Then add 3 parts of Acrylic Polyurethane Base (component A) to 1 part Activator (component B) by volume and mix product thoroughly. Mix only the number of kits that can be used within 1-2 hours. Properly mixed product is ready to apply by brush, roller or spray equipment. The initial viscosity is 25-35 seconds Zahn #2 Cup. Sprayable pot-life is 2-3 hours @ 77°F (25°C). If further reduction is desired, add up to 25% of Colorfast EX ZERO VOC Reducer. To speed up dry time, add 1/2 ounce to 2 ounces of Colorfast EX ZERO VOC Accelerator. NOTE: This will decrease the sprayable pot-life. Do not use with other manufacturers' additives. Keep containers closed tightly when not in use. Do not contaminate product with alcohol or water.

CONTAINS: PCBTF CAS# 98-56-6
Acetone CAS# 67-64-1
HEXAMETHYLENE DIISOCYANATE POLYMER CAS# 28182-81-2

HEALTH & SAFETY: Keep away from heat, hot surfaces, spark, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear Protective gloves/protective clothing/eye protections/face protection. IF ON SKIN: Wash with plenty of water.

FIRST AID: IF ON SKIN: (or hair) Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor/physician if you feel unwell. Specific treatment (see first aid section on this label). If skin irritation persists: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate method to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

PROP 65 WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

RECOMMENDED STORAGE TEMPERATURE: Store indoors at 50°-95°F (10°-35°C). Store in a well-ventilated locked up place. Keep cool. Flash Point (TCC): -4°F (-20°C).

DOT INFORMATION: Paint: Flammable Liquid 3; Packing Group II, UN-1263



DANGER!

**HIGHLY FLAMMABLE LIQUID AND VAPORS
MAY CAUSE DROWSINESS OR DIZZINESS.
CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
HARMFUL IF INHALED.
MAY CAUSE RESPIRATORY IRRITATION.**

KEEP OUT OF REACH OF CHILDREN

AIR QUALITY INFORMATION

Colorfast Activator only formulation data:

Coating VOC Content: 0 g/L (0 lb/gal)
Material VOC Content 0 g/L (0 lb/gal)
VOC partial vapor pressure 0 mmHg @ 68° F

Non-Photochemically Reactive

This product does not contain t-Butyl Acetate (tBAC)

Activator when mixed with Colorfast EX ZERO VOC Acrylic Polyurethane does not increase coating VOC content.

HMS RATINGS

Health	2
Flammability	3
Physical Hazard	0

Modern Masters Inc.
Valencia, CA 91355 USA
(800) 942-3166 • modernmasters.com

© 2016, Modern Masters Inc.
Made in USA

CFEXU 1000032



7 40774 95548 8