



non-fading  
**colorfast**™  
**EX ZERO VOC**  
 acrylic polyurethane  
 colorant

**HMIS RATINGS**

Health	2
Flammability	2
Physical Hazard	0

Modern Masters Inc.  
 Valencia, CA 91355 USA  
 (800) 942-3166  
 modernmasters.com  
 © 2015, Modern Masters Inc.  
 Made in USA

**COLORANT**

1 US Gal. / 3.78 L

Designed to be used with Colorfast EX ZERO VOC Acrylic Polyurethane Clear Base for maximum exterior durability and colorfastness, while maintaining the formulated ZERO VOC SCAQMD “Super Compliancy” rating

**industrial use only**  
 by professional, trained painters.  
 not intended for sale to or use  
 by general public.

**IMPORTANT:** The contents of this package must be blended with components before the product can be used. Follow all mixing instructions below. Before opening the packages read all warning labels, SDS and TDS information. It is recommended to review applicable state and local regulations before using product. Follow all precautions recommended for use of this product.

**MIXING INSTRUCTIONS:** EX ZERO VOC Colorants have been formulated to minimize settling and hard pack during storage. All Colorants are suitable for use with in-store mixing stations. Start mixing 5-10 minutes before beginning to pour and weigh Colorants into Colorfast EX ZERO VOC Acrylic Polyurethane Clear Base (component A). After achieving desired color and gloss, mix in Activator (component B), Reducer and any other Additives prior to application. Never add any reducers or additives directly to Colorant containers. This will weaken tinting strength of Colorant and affect color formulations. Do not use with other manufacturers’ bases or additives. Keep containers closed when not in use. Do not contaminate product with alcohol or water.

**PREPARATION FOR PAINTING:** The surface to be coated shall be clean (free of oil, dust, etc.). Metal surfaces should be primed with one of Modern Masters recommended low VOC epoxy or polyurethane primers or primer surfacers. Consult your technical representative for preparation, application and substrate specific details. Spray equipment must be properly grounded. Clean equipment immediately after use with thinner (SCAQMD compliant equipment cleaner). Production type operations and field application shall be performed only in specifically designated areas with local exhaust ventilation and other environmental control measures as required by OSHA on the basis of an on-site industrial hygiene survey. Touch-up type operations shall be performed only in areas with good general ventilation. Do not expose unprotected personnel in adjacent areas to mist, spray, or vapor.

**CONTAINS:** PCBTF CAS# 98-56-6

**HEALTH & SAFETY:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **MAYBE HARMFUL IF ABSORBED THROUGH SKIN.** Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motor and other sources of ignition during use and until vapors are gone. In case of fire, use Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog to extinguish. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. **USE ONLY OUTDOORS OR WELL-VENTILATION AREA.** Do not breathe vapors or mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist level above applicable limits, wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer’s directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. **EYE CONTACT:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing and get medical attention; **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **INGESTION:** If swallowed, call POISON CENTER or doctor/physician. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent and excess material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

**PROP 65 WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

**RECOMMENDED STORAGE TEMPERATURE:** Store indoors at 50° - 95°F (10°-35°C). Store in a well-ventilated place. Keep cool. Flash Point (TCC): 109°F (43°C).

**DOT INFORMATION: Paint:** Flammable Liquid 3; Packing Group III, UN-1263



**WARNING!**

**FLAMMABLE LIQUID AND VAPORS.  
 MAY CAUSE FLASH FIRE AT HIGH TEMPERATURE**

**EXPOSURE TO VAPORS CAUSES LUNG, SKIN, OR  
 EYE IRRITATION**

**KEEP OUT OF REACH OF CHILDREN**

**AIR QUALITY INFORMATION**

**This product as supplied meets VOC content limits of SCAQMD Rules 1113, 1107, 1136, 1145, 1151.**

**Colorfast Colorant formulation data:**  
 Coating VOC Content: 0 g/L (0 lb/gal)  
 Material VOC Content 0 g/L (0 lb/gal)

Non-Photochemically Reactive

This product does not contain t-Butyl Acetate (tBAC)

**This product contains  
 No Hazardous Air Pollutants**