Always prepare a sample prior to beginning a project

MAX. VOC 875 a/L

Modern Masters Inc. Valencia, CA USA (800) 942-3166 modernmasters.com © 2016, Modern Masters Inc. Made in USA





MM200079 0516

Water Base 32 fl. oz. / 946 ml

Clear

MODERN MASTERS

Decorative Painter's TINTABLE GLAZE

Tint with Universal Colorants
ONE HOUR "OPEN TIME"

Tested & Preferred by Professional Decorative Painters

• For

Use

Professional

Perfect for

Creating All

Faux Finishes

Non-Yellowing

Water Resistant

• A Durable Finish

• 100% Acrylic

coverage | cobertura 150-200

sq ft / qt | pies cuadrados / qt

Drying Time Tiempo de Secado	Recoat: 3 hours <i>Repintar: 30 horas</i>
@ 70% RH	Dry Time: 36 hours Tiempo de Secado: 36 horas
Tomporature and humidity dependent	

Temperature and humidity dependent

Dependiente de temperatura y humedad

Modern Masters *Tintable Glaze* is a professional grade, 100% acrylic, non-yellowing, water base, clear medium. Perfect for creating faux finishes (marbling, wood graining, exotic mineral, etc.) on furniture, cabinetry, decorative moldings and other nonporous surfaces.

SURFACE PREPARATION: *Tintable Glaze* should be applied over a previously painted and fully cured, 100% acrylic semi-gloss latex surface. The surface should be clean and sound.

TINTING: *Tintable Glaze* can be tinted using standard universal colorants. **Do not mix/tint the glaze with paint.** Doing so may drastically accelerate the drying time and/or increase the opacity of the glaze.

APPLICATION: The thicker *Tintable Glaze* is applied, the longer it will stay "open" and workable. Generally the glaze will stay "open" for one hour, depending on color concentration, film thickness and humidity. The cooler and more humid the air, the longer the glaze will stay wet.

PROTECTION: Do not clean unprotected glazed surfaces with harsh chemicals. Surfaces that will be handled should be protected with two coats of Modern Masters *Dead Flat Varnish* for interior surfaces. All exterior surfaces should be protected with *Exterior Dead Flat Varnish*. Follow the instructions on the container label.

CLEAN UP: Clean tools, brushes and equipment with warm, soapy water immediately. Promptly wipe up spills and splatters with a damp cloth.

HANDLING & STORAGE: When not in use, close container and store at room temperature. Protect product from freezing or extreme heat. Do not reuse this container and dispose of empty container properly.

HEALTH & SAFETY: Use in a well ventilated area. Avoid contact with eyes. Wash hands after use. Do not take internally. When spraying or sanding use NIOSH approved respirator.

KEEP OUT OF REACH OF CHILDREN

WARRANTY: This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit modernmasters.com for Technical Data Sheets, Material Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.