



THEME PAINT™

EXTERIOR DEAD FLAT VARNISH

Clear Water Base
UV Protective Coat for
Rockwork, Colorwashes
and other Faux Finishes

1 US Gal. / 3.78 L

- Non-Yellowing
- Abrasion Resistant
- Water Resistant
- UV Protective
- Brush, Roll or Spray Apply

COVERAGE COBERTURA 350-450 sq ft / gal pies cuadrados / gal
Minimum two coats recommended <i>Se recomienda un minimo de dos capas</i>

Drying Time <i>Tiempo de Secado</i> @ 50% RH	60°F
	Touch: 30 minutes <i>Tacto: 30 minutos</i> Recoat: 2 hours <i>Repintar: 2 horas</i>
Temperature and humidity dependent <i>Dependiente de temperatura y humedad</i>	

Modern Masters Theme Paint Exterior Dead Flat Varnish is a low VOC, 100% acrylic, non-yellowing, water base, protective clear top coat formulated with maximum levels of UV Blockers and UV Absorbers to further reduce the effects of harmful ultraviolet rays. It's clear, dead flat finish will eliminate any undesired sheen variations on the painted project. Not recommended for use over **Metallic Paint Collection™** paints or **Metal Effects®** oxidized finishes.

SURFACE PREPARATION: The painted surface must be fully cured prior to application (approx. 24 hours). If applying over porous surfaces, (such as stone and plaster surfaces) dilute varnish 10% with water and apply in thin coats until the surface is sealed. **Not intended for use over oil base finishes.**

APPLICATION METHODS: *Theme Paint Exterior Dead Flat Varnish* can be applied by brush, roller, or HVLP spray gun. Do not apply when air and surface temperatures are below 50°F (10°C) or high humidity conditions exist. Optimal application conditions are 60°F-80°F (16°C-27°C) and 30%-60% relative humidity. For most applications thinning is unnecessary. Stir before use. Do not shake. **Brushing:** Use a high-quality synthetic bristle brush. **Rolling:** Use a high-quality, soft, short-nap roller. **Spraying:** Use a HVLP gun, conventional cup gun or airless spray system. If thinning is necessary, add up to 10% (12 fl. oz. (354 ml) of water per gallon (3.78 L) of *Exterior Dead Flat Varnish*. For best results and maximum protection, a minimum of two coats is recommended.

CLEAN UP: Clean tools, brushes, rollers and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

HANDLING & STORAGE: When not in use, close container tightly and store at room temperature. Protect from freezing and extreme heat. If contents freeze, allow thawing at room temperature. Do not reuse container and dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

HEALTH & SAFETY: Use in a well-ventilated area. Avoid contact with eyes. Wash hands thoroughly with soap and warm water after use. Do not take internally. When spraying or sanding, use a properly-fitted, NIOSH approved respirator per the manufacturer's instructions.

KEEP OUT OF REACH OF CHILDREN

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT: This product will perform as claimed if directions are followed. Directions

are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

TECHNICAL ASSISTANCE: For additional technical assistance contact our Technical Department at 800-942-3166 or email technical@modernmasters.com.

Visit modernmasters.com for Technical Data Sheets, Material Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.

MAX. VOC 100 g/L
This product meets SCAQMD Rule 1113-Architectural coatings; Faux Finishing category - Clear Topcoat
This product can only be sold as part of a Faux Finishing coating system.

Modern Masters Inc.
Los Angeles, CA USA
(800) 942-3166
modernmasters.com

© 2015, Modern Masters Inc.
Made in USA