



MAX. VOC 100 g/L  
This product meets SCAQMD Rule  
1113-Architectural coatings;  
Faux Finishing category -  
Clear Topcoat

This product can only be used  
as part of a Faux Finishing coating system.

Modern Masters Inc.  
Valencia, CA 91355 USA  
(800) 942-3166  
[modernmasters.com](http://modernmasters.com)

© 2016, Modern Masters Inc.  
Made in USA



*protects*

VENETIAN  
P L A S T E R

TOPCOAT

Protective Sealer for Venetian Plaster

Clear

Water Base

1 US Gal. / 3.78 L

Low VOC



Protects While  
Maintaining a  
Polished Stone Effect  
with Venetian Plaster

- Water Resistant
- Durable
- Water Base

COVERAGE | *COBERTURA*

**800-1200**

sq ft / gal

*pies cuadrados / gal*

**Modern Masters® Venetian Plaster Topcoat**  
is used as a protective sealer over a dry  
**Venetian Plaster** finish. High traffic areas  
where washability is imperative or rooms that  
experience high humidity, such as bathrooms,  
should be sealed with Topcoat. Other protective  
topcoats cannot be used to protect the *Venetian  
Plaster*.

**SURFACE PREPARATION:** After sanding the  
*Venetian Plaster*, wipe the surface with a damp  
rag to eliminate any dust. Allow the surface to  
dry.

**APPLICATION:** *Venetian Plaster Topcoat* is  
applied using a trowel (it cannot be rolled,  
brushed or spayed on). Hold the trowel at a 60  
degree angle and scrape a very thin layer of  
the topcoat onto the dry Venetian Plaster finish.  
Scrape off any excess using a clean trowel and  
let this coat dry. This application will darken  
the color slightly and dry to a satin sheen. The  
topcoat can be slightly polished once it is dry by  
rubbing it with the flat side of a clean trowel.

For a translucent metallic sheen over the finished  
*Venetian Plaster*, use **Pearl Topcoat**. Mix well  
and apply with a trowel over the dry *Venetian  
Plaster* in the same manner described above.



Drying Time

*Tiempo de Secado*

@ 50% RH

**55°F+**

Dry Time: 1-2 hours

*Tiempo de Secado 1-2 horas*

Temperature and humidity dependent

*Dependiente de temperatura y humedad*

**CLEAN UP:** Clean tools, with warm, soapy water  
immediately after use. Promptly wipe up spills  
and splatters with a damp cloth.

**HANDLING & STORAGE:** When not in use,  
close container tightly and store at room  
temperature. Protect from freezing and extreme  
heat. If contents freeze, allow thawing at room  
temperature. Do not reuse container and dispose  
of unused or unwanted product in accordance  
with local laws regulating water base coatings.

**HEALTH & SAFETY:** Use in a well ventilated area.  
Avoid contact with eyes. Wash hands after use.  
Do not take internally. When sanding use NIOSH  
approved respirator. Refer to MSDS for additional  
health and safety information.

**KEEP OUT OF REACH OF CHILDREN**

**WARRANTY:** This product will perform as  
claimed if directions are followed. Directions are  
as complete as possible, but cannot encompass  
all conditions, applications, techniques, and/or  
surfaces, which are beyond our control. Warranty  
is limited to replacement or refund value of  
product actually used, if such product proves  
defective within two years of manufacture. No  
other warranty is expressed or implied.

Visit **[modernmasters.com](http://modernmasters.com)** for Technical Data  
Sheets, Material Safety Data Sheets, Application  
Instructions and the latest information on all our  
specialty water base paints and coatings.