

 **RUST-OLEUM**
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-942-3166 modernmasters.com

Made in USA | Hecho en E.U.A.

©2018 Rust-Oleum Corp. and Wildfire Inc. 345338 0918

WF30732



M | M
MODERN
MASTERS®



**WILDFIRE
LIGHTING**
IGNITE YOUR IMAGINATION

**SHEEN
LEVELER**

TRANSPARENT WATER-BASE POLYURETHANE

FLAT SHEEN • NON YELLOWING • LOW VOC
SPECIFICALLY FORMULATED
FOR USE WITH WILDFIRE LUMINESCENT PAINTS

1 Qt | 946 mL

WILDFIRE BRAND PAINTS AND COATINGS

THE PROFESSIONAL ARTISTS CHOICE

Originally developed for the scenic studios of Hollywood to create dramatic visual effects for film, television and amusement parks, Wildfire brand paint and coating products have become the standard of quality for the visual effects professional. Designed to eliminate the visible variation in sheen between the painted image and the surrounding area, Wildfire Sheen Leveler is the ideal protective top coating for all Wildfire Luminescent Clear Color Paints. Wildfire Sheen Leveler dries quickly to a smooth low sheen flat finish that is water resistant and flexible.

WHERE TO USE For use over invisible clear colors only. Images created with Invisible Clear Colors may still be detected in visible light due to variations in the sheen. For example, a stenciled image over a dead flat surface. To eliminate the visible variation in sheen apply "Sheen Leveler" over the painted image and the surrounding area.

SURFACE PREPARATION Allow your project to dry for 24 to 48 hours before applying Sheen Leveler. Painted surface should be clean, dry and fully cured prior to application. Apply on a small test area to ensure desired effect is achieved.

APPLICATION METHODS Product is ready to use, do not dilute with water. For best results apply with an airbrush, HVP spray equipment, artist brushes or varnish roller. Apply one or two coats of Sheen Leveler over the entire completed project for total invisibility. Do not apply when air and surface temperatures are below 50° F (10° C) or high humidity conditions exist. Optimal conditions are 60° F (16° C) to 80° F (27° C) and 30% to 60% relative humidity. Stir thoroughly before use, do not shake.

COVERAGE Sheen Leveler covers approx. 75-100 sq. ft / quart, 6.75-9.0 M² / 946ml.
DRY TIMES Dry-to-touch is approximately 30 minutes, re-coat time is approximately 2 hours. The dry time will vary with temperature and humidity.

CLEANUP Clean tools, brushes and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

HANDLING & STORAGE Store Wildfire Sheen Leveler out of direct sunlight. To avoid skinning, close container after each use. Keep lid tightly closed during storage. Protect from freezing.



HEALTH & SAFETY Ensure fresh air entry during application and drying. Avoid contact with eyes, skin and clothing. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted (NIOSH approved) respirator. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. Refer to product SDS for additional health and safety information.

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

KEEP OUT OF REACH OF CHILDREN

SATISFACTION GUARANTEED Rust-Oleum guarantees your complete satisfaction with this product's performance when applied to properly prepared surfaces in accordance with label instructions. If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-942-3166 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

MAX. VOC 150 g/L



Wildfire® and its symbol are registered trademarks of Wildfire Inc., Torrance, CA
wildfirelighting.com