



**MODERN MASTERS®  
DECORATIVE PAINTER'S TINTABLE GLAZE**

**DESCRIPTION AND USES**

Modern Masters® Tintable Glaze is a professional grade, 100% acrylic, non-yellowing, water-based, clear medium. Perfect for creating faux finishes (marbling, wood graining, exotic mineral, etc.) on furniture, cabinetry, decorative moldings and other nonporous surfaces.

**PRODUCT**

SKU	DESCRIPTION (32 oz.)
DP60832	Decorative Painter's Tintable Glaze

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Tintable Glaze should be applied over a previously painted and fully cured, 100% acrylic semi-gloss latex surface. The surface should be clean and sound.

**NOTE:** Not intended for use over oil base finishes.

**TINTING:** Tintable Glaze can be tinted using standard universal colorants. Stir in colorants to fully incorporate them into the glaze.

**APPLICATION**

**NOTE:** Always test the product in a small, inconspicuous area before beginning a project. We recommend preparing a sample board prior to beginning a project to check color and technique. The glaze should be mixed thoroughly before using.

Tintable Glaze can be applied by brush, roller or other decorative tool. Do not apply when air and surface temperature are below 50°F (10°C) or high humidity conditions exist. Optimal application conditions are 50-80°F (10-27°C) and 30-60% relative humidity.

The thicker Tintable Glaze is applied, the longer it will stay "open" and workable. Generally the glaze will stay "open" for one hour, depending on color concentration, film thickness and humidity. The cooler and more humid the air, the longer the glaze will stay wet.

**PRODUCT APPLICATION (cont.)**

**PROTECTION:** Do not clean an unprotected glazed surface with harsh chemicals. Surfaces that will be handled should be protected with two coats of Modern Masters Dead Flat Varnish for interior surfaces. All exterior surfaces should be protected with Exterior Dead Flat Varnish. Follow the instructions on the container label.

**DRY TIMES:** The colored glaze will dry to an eggshell sheen in approximately 3 hours and fully cure in 24 hours.

**NOTE:** Lower temperature and/or higher humidity will lengthen the dry and cure times.

**COVERAGE:** Approximately 150-200 sq. ft./qt., 13.9-18.5m<sup>2</sup>/946 mL.

**CLEAN UP:** Clean tools with soap and warm water immediately after use. Promptly wipe up any spills and splatters with a damp cloth. Do not reuse containers and properly dispose of empty containers.

**HANDLING & STORAGE:** When not in use, close container tightly and store at room temperature. Protect product from freezing and from extreme heat. Do not reuse this container and dispose of empty container properly.

**DISPOSAL:** Dispose of unused or unwanted product in accordance with local laws regulating water-based coatings.

	<b>TECHNICAL DATA</b>	<b>MDM-32</b>
	<b>MODERN MASTERS®</b> <b>DECORATIVE PAINTER'S TINTABLE GLAZE</b>	

**PHYSICAL PROPERTIES**

		DECORATIVE PAINTER'S TINTABLE GLAZE
<b>Resin Type</b>		Water-based Acrylic
<b>Pigment Type</b>		Fumed silica
<b>Solvents</b>		Water
<b>Weight</b>	<b>Per Gallon</b>	8.61 lbs.
	<b>Per Liter</b>	1.03 kg
<b>Solids</b>	<b>By Weight</b>	11.83%
	<b>By Volume</b>	10.35%
<b>Volatile Organic Compounds</b>		859 g/L
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		1 mils
<b>Wet Film to Achieve DFT (Unthinned material)</b>		9.7 mils
<b>Practical Coverage at Recommended DFT (assume 15% material loss)</b>		150-200 sq. ft./qt.
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	3 hours
	<b>Handle</b>	4 hours
	<b>Recoat</b>	8 hours
	<b>Full Cure</b>	24 hours
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		>200°F
<b>Safety Information</b>		<b>PROTECT FROM FREEZING - NOT FREEZE THAW STABLE</b> For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.