



colorfast^{non-fading} EX zero VOC acrylic polyurethane accelerator

industrial use only
by professional, trained painters.
not intended for sale to or use by general public.

ACCELERATOR

1 US QUART / 946 ml

IMPORTANT: Colorfast EX ZERO VOC Accelerator is intended as an additive for pre-mixed and activated Colorfast EX ZERO VOC Acrylic Polyurethane Base. Before opening and using this product read all warning labels, SDS and TDS information. It is recommended to review applicable state and local regulations before using product. Follow all precautions recommended for this product.

MIXING INSTRUCTIONS: Properly mixed and activated Colorfast EX ZERO VOC Acrylic Polyurethane Base is ready to apply by brush, roller or spray equipment. The initial viscosity is 25-35 seconds Zahn #2 Cup. Sprayable pot-life is 2-3 hours @ 77°F (25°C). If a reduced dry time is desired add 1/2 ounce to 2 ounces of Accelerator to the pre-mixed and activated Colorfast EX ZERO VOC Acrylic Polyurethane base. Note: The addition of Accelerator will reduce the sprayable pot-life of the paint. If too much is added it can cause reduced adhesion, change the physical properties and the appearance of the coating. Do not use with other manufacturers' product. Keep containers closed tightly when not in use. Do not contaminate product with alcohol or water.

CONTAINS: PCBTf CAS# 98-56-6
Acetone CAS# 67-64-1

HEALTH & SAFETY: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **MAYBE HARMFUL IF ABSORBED THROUGH SKIN.** Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motor and other sources of ignition during use and until vapors are gone. In case of fire, use Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog to extinguish. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. **USE ONLY OUTDOORS OR WELL-VENTILATION AREA.** Do not breathe vapors or mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist level above applicable limits, wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Causes serious eye irritation. Suspected of causing genetic defects. May damage fertility or the unborn child. Causes damage to organs. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction.

FIRST AID: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. **EYE CONTACT:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing and get medical attention; **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **INGESTION:** If swallowed, call POISON CENTER or doctor/physician. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent and excess material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

PROP 65 WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

RECOMMENDED STORAGE TEMPERATURE: Store indoors at 50°-95°F (10°-35°C). Store in a well-ventilated place. Keep cool.
Flash Point (TCC): 109°F (43°C).

DOT INFORMATION: Paint: Flammable Liquid 3; Packing Group III, UN-1263



WARNING!

**FLAMMABLE LIQUID AND VAPOR
VAPOR MAY BE HARMFUL. MAY CAUSE IRRITATION PROLONGED OR
REPEATED CONTACT OF LIQUID OR BREATHING OF VAPORS OR
MISTS MAY CAUSE DELAYED AND SERIOUS INJURY**

KEEP OUT OF REACH OF CHILDREN

AIR QUALITY INFORMATION

Colorfast Accelerator only formulation data
Coating VOC Content: 0 g/L (0 lb/gal)
Material VOC Content 0 g/L (0 lb/gal)
VOC partial vapor pressure 0 mmHg @ 68° F

Non-Photochemically Reactive

This product does not contain t-Butyl Acetate (tBAC)
Activator when mixed with Colorfast EX ZERO VOC Acrylic Polyurethane does not increase coating VOC content.

HMIS RATINGS

Health	2
Flammability	2
Physical Hazard	0

Modern Masters Inc.
Valencia, CA 91355 USA
(800) 942-3166 • modernmasters.com

© 2016, Modern Masters Inc.
Made in USA

CFEXA 1060132



283947 0416