



# colorfast<sup>non-fading</sup> EX ZERO VOC acrylic polyurethane reducer

**industrial use only**  
by professional, trained painters.  
not intended for sale to or use by general public.

## REDUCER

1 US QUART / 946 ml

**IMPORTANT:** Colorfast EX ZERO VOC Reducer is intended as a thinner for pre-mixed and activated Colorfast EX ZERO VOC Acrylic Polyurethane Base. Before opening and using this product read all warning labels, SDS and TDS information. It is recommended to review applicable state and local regulations before using product. Follow all precautions recommended for this product.

**MIXING INSTRUCTIONS:** Properly mixed and activated Colorfast EX ZERO VOC Acrylic Polyurethane Base is ready to apply by brush, roller or spray equipment. The initial viscosity is 25-35 seconds Zahn #2 Cup. Sprayable pot-life is 2-3 hours @ 77°F (25°C). If further reduction is desired, add up to 25% of Colorfast EX ZERO VOC Reducer. Do not use with other manufacturers' product. Keep containers closed when not in use. Do not contaminate product with alcohol or water.

**CONTAINS:** PCBTF CAS# 98-56-6  
Acetone CAS# 67-64-1

**HEALTH & SAFETY:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **MAYBE HARMFUL IF ABSORBED THROUGH SKIN.** Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motor and other sources of ignition during use and until vapors are gone. In case of fire, use Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog to extinguish. Prevent build-up of vapors by opening all windows and doors to achieve cross ventilation. **USE ONLY OUTDOORS OR WELL-VENTILATION AREA.** Do not breathe vapors or mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist level above applicable limits, wear an appropriate properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. May cause respiratory irritation. Causes skin irritation.

**FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. **EYE CONTACT:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing and get medical attention; **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. **INGESTION:** If swallowed, call POISON CENTER or doctor/physician. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent and excess material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

**PROP 65 WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

**RECOMMENDED STORAGE TEMPERATURE:** Store indoors at 50°-95°F (10°-35°C). Store in a well-ventilated place. Keep cool. Flash Point (TCC): -4°F (-20°C).

**DOT INFORMATION: Paint:** Flammable Liquid 3; Packing Group II, UN-1263



**DANGER!**  
**HIGHLY FLAMMABLE LIQUID AND VAPORS  
MAY CAUSE FLASH FIRE**  
**EXPOSURE TO VAPORS CAUSES SERIOUS EYE IRRITATION. TOXIC IF  
INHALED. MAY CAUSE DROWSINESS OR DIZZINESS.**

**KEEP OUT OF REACH OF CHILDREN**

#### AIR QUALITY INFORMATION

**Colorfast Reducer only formulation data:**

Coating VOC Content: 0 g/L (0 lb/gal)

Material VOC Content 0 g/L (0 lb/gal)

VOC partial vapor pressure 0 mmHg @ 68° F

Non-Photochemically Reactive

This product does not contain t-Butyl Acetate (tBAC)

Reducer when mixed with Colorfast EX ZERO VOC Acrylic Polyurethane does not increase coating VOC content.

#### HMS RATINGS

Health	2
Flammability	4
Physical Hazard	0

Modern Masters Inc.  
Valencia, CA 91355 USA  
(800) 942-3166 • [modernmasters.com](http://modernmasters.com)

© 2016, Modern Masters Inc.  
Made in USA

**CFEXR1000132**

