

MAX. VOC 350 g/L.

This product can only be sold as part of a Faux Finishing coating system.

Not intended for sale or use in the South Coast Air Quality Management District.

Modern Masters Inc.
Valencia, CA 91355 USA
(800) 942-3166
modernmasters.com

© 2015, Modern Masters Inc.
Made in USA




Decorative Painter's DEAD FLAT VARNISH

*Clear Water Base Interior Finish Coat for
Eliminating Sheen on Faux & Decorative Finishes*

Water Base


1 US Gal. / 3.78 L

Non-Yellowing



- Optimum Clarity
- No Sheen
- For Interior Use
- Brush, Roll or Spray Apply

COVERAGE COBERTURA 350-450 sq ft / gal <i>pies cuadrados / gal</i>
Minimum two coats recommended <i>Se recomienda un minimo de dos capas</i>

 Drying Time <i>Tiempo de Secado</i> @ 50% RH	60°F+
	Touch: 30 min. <i>Tacto: 30 minutos</i> Recoat: 2 hours <i>Repintar: 2 horas</i>
Temperature and humidity dependent <i>Dependiente de temperatura y humedad</i>	

Modern Masters **Dead Flat Varnish** is a premium quality, 100% acrylic, non-yellowing, water base clear finish coat formulated to have the optimum level of clarity with the least amount of sheen. **Dead Flat Varnish** will remove undesirable variations in sheen created by using semi-gloss base coats with Decorative Glazes and allows the finish to maintain that aged effect. It is water resistant and abrasion resistant. Not recommended for use over **Metallic Paint Collection™** or **Metal Effects® oxidized finishes**.

SURFACE PREPARATION: The underlying faux finish or decorative painted surface must be fully cured prior to application (approx. 24 hours). If applying over porous surfaces, (such as stone and plaster finishes) dilute varnish 10% with water and apply in thin coats until the surface is sealed. **Not intended for use over oil base finishes.**

APPLICATION: *Dead Flat Varnish* can be applied by brush, roller or spray equipment. Do not apply when air and surface temperatures are below 50°F (10°C) or high humidity conditions exist. Optimal application conditions are 60°F-80°F (16°C- 27°C) and 30%-60% relative humidity. For most applications

thinning is unnecessary. Stir thoroughly before use. **Do not shake.** **Brushing:** Use a high-quality synthetic bristle brush. **Rolling:** Use a high-quality, soft short-nap roller. **Spraying:** Use a HVLP gun, conventional cup gun or airless spray system. If thinning is necessary, add up to 10% (12 fl. oz./355 ml) of water per gallon/3.78 L of *Dead Flat Varnish*. For exterior surfaces, use **Exterior Dead Flat Varnish**.

CLEAN UP: Clean tools, brushes and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

HANDLING & STORAGE: When not in use, close container tightly and store at room temperature. Protect from freezing and extreme heat. If contents freeze, allow thawing at room temperature. Do not reuse container and dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

HEALTH & SAFETY: Use in a well ventilated area. Avoid contact with eyes. Wash hands thoroughly with soap and warm water after use. Do not take internally. When spraying or sanding, use a properly fitting (NIOSH approved) respirator per the manufacturer's instructions.

KEEP OUT OF REACH OF CHILDREN

WARRANTY: This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit modernmasters.com for Technical Data Sheets, Material Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.