



Platinum[™] SERIES

GLAZING CREAM COLORS

Modern Masters Inc.
Valencia, CA 91355 USA
(800) 942-3166

modernmasters.com

© 2015, Modern Masters Inc.
Made in USA

Made
in USA

16 fl. oz. | 473 ml

Modern Masters' Platinum Series Glazing Colors are slow-drying, water base, high strength, pre-colored glazes, formulated for the utmost in controlled color strength with a smooth, fluid consistency for decorative painting techniques.

Used as a tinting medium for **Platinum Series-Wall Glazing Cream** or **Furniture & Cabinetry Glazing Cream**. **Glazing Colors** can be mixed in any ratio, into either **Glazing Cream**, to achieve the precise properties of pigment load and transparency.

CLEAN UP: Clean tools, brushes and equipment with warm, soapy water immediately. Promptly wipe up spills and splatters with a damp cloth.

HANDLING & STORAGE: When not in use, close container and store at room temperature. Protect product from freezing or extreme heat. Do not reuse this container and dispose of empty container properly.

HEALTH & SAFETY: Use in a well ventilated area. Avoid contact with eyes. Wash hands after use. Do not take internally. When spraying or sanding, use NIOSH approved respirator. **CONTAINS NO HAZARDOUS AIR POLLUTANTS.**

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead.

KEEP OUT OF REACH OF CHILDREN

WARRANTY: This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit modernmasters.com for Technical Data Sheets, Material Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.

MAX. VOC 350 g/L

This product meets SCAQMD
Rule 1113-Architectural coatings:
Faux Finishing category - Glazes