


MAX. VOC 50 g/L



# MasterClear<sup>®</sup> Supreme

## the ultimate protective clear coat



Modern Masters Inc.  
Valencia, CA 91355 USA  
(800) 942-3166  
modernmasters.com

© 2015, Modern Masters Inc.  
Made in USA



<50 g/L VOC  
No HAPS

**Multi-Surface**  
**Interior and Exterior**  
**Acrylic/Aliphatic**  
**Polycarbonate-Polyurethane**  
**Matte**

UV RESISTANT

1 US Gal. / 3.78 L

LOW VOC

- Self-Crosslinking Technology
- Ultimate UV Protection
- LEED Specified - EQ Credit 4.2
- Exceeds ALL National and Regional VOC Regulations

<b>COVERAGE   COBERTURA</b> <b>300-400</b> sq ft / gal   pies cuadrados / gal
Minimum two coats recommended <i>Se recomienda un minimo de dos capas</i>

Drying Time <i>Tiempo de Secado</i> @ 50% RH	<b>55°F+</b>
	Touch: 30 min.   <i>Tacto: 30 minutos</i>
Recoat: 1-2 hours   <i>Repintar: 1-2 horas</i>	
Temperature and humidity dependent <i>Dependiente de temperatura y humedad</i>	

**MasterClear<sup>®</sup> Supreme** is a water base self-crosslinking acrylic/aliphatic polycarbonate-polyurethane protective topcoat that dries quickly to a durable clear finish. **Advanced Resin Technologies** protect **Interior Surfaces** against abrasion, scuffing, chipping, water, alcohol, household chemicals, plus it protects **Exterior Surfaces** from oxidation, salt air, chlorine, acid rain, bird droppings, mildew, etc. **MasterClear Supreme** has outstanding gloss retention and clarity with added **UV Blockers and Absorbers** that greatly reduce the sun's graying and fading effects on stained wood and most painted surfaces, keeping them looking fresh for years. The **Innovative Low-VOC Formula** has very little odor and exceeds all National and Regional VOC category requirements!

**Sheen: Matte – measured 10-20 @ 60°**

**WHERE TO USE:**

**Interiors:** Protects most painted surfaces, wallpaper, bare wood, oil and water base stained wood, doors, columns, cabinetry, window sills, mantels, wainscot, wood paneling, crown molding, baseboards, chair rails, furniture and picture frames. It is a perfect clear coat for faux marble and wood grained surfaces.

**Exteriors:** UV and weather resistant, it extends the life of most previously painted surfaces, stained or unstained wood and aluminum surfaces such as doors, porch surrounds and supports, decorative moldings, painted façades, murals, garage doors, anodized aluminum window casings, aluminum paneling, outdoor furniture, and garden ornaments.

**MasterClear Supreme is not recommended for surfaces painted with Metallic Paint Collection™, white or light colored surfaces or for use on floors.**

**SURFACE PREPARATION:** Painted surfaces should be fully cured prior to application, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, and other contaminants. **Taping:** Use high quality, low-tack tape when taping over surfaces that have been previously painted and fully cured. **Bare Wood** should be prepared by first sanding the surface smooth, removing dust with a vacuum and then wiping the surface clean with an

oil-free tack cloth. Moisten the wood surface with a wet towel or sponge and allow it to dry. When dry, sand the raised grain with fine sandpaper until smooth, then vacuum and wipe clean with the oil-free tack cloth. **Oil Base or Water Base Stained Wood:** Follow stain manufacturer's instructions for application and dry times for clear coating with a water base poly. Make sure the stain has been wiped off the surface completely and has dried a minimum of 24 hours before applying **MasterClear Supreme**. **Aluminum:** Clean the aluminum. The amount of cleaning will depend on the condition of the anodized aluminum. If window frames or extruded anodized aluminum is just dull or faded, it can be washed with mild soap and water. Use microfiber cloths which are inexpensive and will clean the metal very effectively. If the anodized aluminum is pitted or stained, use a no-scratch cleanser or synthetic steel wool made by 3M (do not use regular steel wool, small pieces can remain on window frames and will rust). Rinse well. Let dry. If any oxidation remains, wipe with the microfiber cloth. Finally, wipe down the anodized aluminum with denatured alcohol and wear neoprene gloves to protect your hands.

**APPLICATION METHODS:** Stir thoroughly before use, do not shake. **MasterClear Supreme** can be brushed, rolled, or spray applied. Sand between coats to achieve the smoothest finish. Optimal conditions are 60°F/16°C to 80°F/27°C and 30% to 60% relative humidity. **Brushing:** Use a high-quality synthetic bristle brush. **Rolling:** Use a high-quality short-nap varnish roller. **Spraying:** To spray, dilute with up to 10% water (12 fl. oz. /360 ml of water to 1 Gal./3.78 L of **MasterClear Supreme**). Use an HVLP gun, conventional cup gun or airless spray system with a fine tip. **Do not apply in temperatures below 55°F/13°C or above 85°F/29°C. Allow to fully cure 7 to 10 days.**

**CLEAN UP:** Clean brushes, rollers, tools, and equipment with warm, soapy water immediately after use. Do not reuse containers and properly dispose of empty containers.

**HANDLING & STORAGE:** To avoid skinning, close container after each use. Keep lid tightly closed during

storage. Keep away from excessive heat. Protect from freezing. If contents freeze, allow thawing at room temperature before use. Stir thoroughly before use. Dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

**HEALTH & SAFETY:** Use in a well-ventilated area. Avoid contact with eyes. Wash hands thoroughly with soap and warm water after use. Do not take internally. When spraying or sanding, use a properly fitting, NIOSH approved respirator per the manufacturer's instructions.

**Skin Contact:** Thoroughly wash with soap and warm water before the coating dries. Individuals with sensitive skin may require gloves.

**Eye Contact:** Rinse with clean water for 15 minutes. Seek medical attention.

**Inhalation:** Use in well-ventilated areas. If irritation occurs, move to fresh air. If irritation persists, seek medical attention.

**Ingestion:** Do not induce vomiting. Seek medical attention.

**Read the Material Safety Data Sheet for Additional Health and Safety Information**

**KEEP OUT OF REACH OF CHILDREN**

**WARRANTY:** This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, application, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit [modernmasters.com](http://modernmasters.com) for Technical Data Sheets, Material Safety Data Sheets, Application Instructions, and the latest information on all our specialty water base paints and coatings.