


MAX. VOC 903 g/L

open time

Metallic Paint  
COLLECTION™

# Extender

for Rolling



Extends “wet-edge” time  
to avoid lapping

Maintains viscosity & shimmer

For Use With  
Metallic Paint Collection™ Colors

Interior/Exterior

1 US Gal. / 3.78 L

Water Base

Modern Masters Inc.  
Valencia, CA 91355 USA  
(800) 942-3166  
[modernmasters.com](http://modernmasters.com)

© 2016, Modern Masters Inc.  
Made in USA

The key to successfully applying Modern Masters *Metallic Paint* with a roller is the ability to “back-roll” the finish before it dries. Because of the high solids (pigments and binders) content and low VOC (volatile organic compound) content in Modern Masters *Metallic Paint*, the addition of a slow-drying *EXTENDER* is necessary. **Extender for Rolling** gives extra “wet-edge” time, without thinning or compromising the integrity of the *Metallic Paint*.

**APPLICATION METHODS:** To roll *Metallic Paint Collection™* colors, add up to 16 oz./473 ml of *Extender for Rolling* to one gallon/3.78 L of *Metallic Paint*. This addition extends the “wet-edge” time necessary to avoid lapping. Use the Modern Masters *Metallic Paint Roller* for large surfaces. Use a 4” “sausage roller” (e.g. Whizz™) with a 1/2” nap for cutting in corners, ceilings and baseboards. Work in approximately 4’ wide sections. Keep a “wet-edge” and finish the surface by back-rolling in one direction, ceiling to floor.

**DRY TIME:** 16 fl. oz./473 ml of *Extender for Rolling* mixed with one gallon/3.78 L of *Metallic Paint* gives approximately 1/2 hour of “wet-edge” time; 1 hour until re-coat; 5 hours until dry-to-touch; and 48 hours for full cure. (Drying times were recorded at 75°F/24°C and 73% R.H.)

**CLEAN UP:** Clean brushes, rollers, tools and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

**HANDLING & STORAGE:** When not in use, close container tightly and store at room temperature. Protect from freezing and extreme heat. If contents freeze, allow thawing at room temperature. Do not reuse container and dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

**HEALTH & SAFETY:** Use in a well-ventilated area. Avoid contact with eyes. Wash hands thoroughly with soap and warm water after use. Do not take internally.

**Read the Material Safety Data Sheet for Additional Health and Safety Information.**

**KEEP OUT OF REACH OF CHILDREN**

**WARRANTY:** This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit [modernmasters.com](http://modernmasters.com) for Technical Data Sheets, Material Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.