



# Luster

Create Beautiful Shimmering Wall Finishes



## SHIMMERSTONE®

Tintable Decorative Architectural Coating

White Tint Base

124 fl. oz | 3.66 L

Water Base

MAX. VOC 50 g/L.

This product meets SCAQMD Rule 1113-Architectural coatings; Faux Finishing category - Trowel Applied Coatings

Modern Masters Inc.  
Valencia, CA 91355  
(800) 942-3166  
[modernmasters.com](http://modernmasters.com)

© 2016, Modern Masters Inc.  
Made in USA

<b>BASIC TOOLS</b> <b>HERRAMIENTAS</b> <b>BÁSICAS</b> 
Trowel/Sea Sponge Roller <i>Llana/Rodillo de Esponja Marina</i>

<b>COVERAGE   COBERTURA</b> <b>240-320</b> sq ft / gal <i>pies cuadrados / gal</i>
Depends on tools and techniques. <i>Depende de herramientas y técnicas.</i>

	Drying Time <i>Tiempo de Secado</i> @ 70% RH	<b>60°F+</b>
	Dry to touch in 1-2 hours. Recoat in 2-3 hours. Dry times will vary depending on temperature, humidity and film thickness. <i>Seco al tacto en 1-2 horas. Repintar en 2-3 horas. El tiempo para secar variará dependiendo en la temperatura, humedad y grosor de las capas de pintura.</i>	

**ShimmerStone** is trowel applied, durable, water resistant, mold & mildew resistant and will adhere to any primed surface. The pearl white Tintable Base can be used as is or tinted using Universal Colorant. The container is short-filled to allow for tinting. Do not exceed 4 fl. oz. of colorant / 124 fl. oz. Alternatively, *Metallic Paint Collection* colors can be used to color the *ShimmerStone* base. Do not exceed 12oz. *Metallic Paint* / 124 fl. oz. Do not store product mixed with *Metallic Paints*. *ShimmerStone* can also be used to lighten *Pre-Mixed Metallic Plaster*.

**SURFACE PREPARATION:** The surface should be free of imperfections, sealed with an acrylic primer-sealer and have a low sheen. We recommend *Zinsser's Bulls Eye 1-2-3*. Allow the primed surface to dry completely, preferably overnight.

**APPLICATION:** **Stir the product thoroughly before use.** *ShimmerStone* can be used to create a wide variety of decorative finishes by using various tools and techniques. **View application videos and get inspired at [modernmasters.com](http://modernmasters.com).**

**CLEAN UP:** Clean trowels, rollers, brushes, etc. with soap and warm water immediately after use. Promptly wipe up spills and splatters with a damp cloth. Do not pour unused contents down the drain. Do not reuse containers and properly dispose of empty containers.

**HANDLING & STORAGE:** Tightly close container when not in use. Store the product in a cool dry place, away from direct sunlight. If contents freeze, allow thawing at room temperature. **Stir well before use.** **Disposal:** Dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

**HEALTH & SAFETY:** Use in a well-ventilated area. Avoid contact with eyes. Wash hands thoroughly with soap and warm water after use. Do not take internally. When spraying or sanding, use a properly-fitting, NIOSH approved respirator per the manufacturer's instructions.

**KEEP OUT OF REACH OF CHILDREN**  
**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust.

LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**WARRANTY:** This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Product Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture.