



THEME PAINT™

Pre-Mixed Color

100% Acrylic
Exterior/Interior
Flat

1 US Gal. / 3.78 L

- Non-Yellowing 100% Acrylic Binders
- Latest Technology in Lightfast Pigments
- Less Than 50 grams/Liter V.O.C.
- Brush, Roll or Spray Apply
- Perfect For Color Retentive Washes

SPREAD RATE UP TO
RENDIMIENTO TEÓRICO

400

sq ft / gal | *pies cuadrados / gal*

| | |
|--|---|
|  Drying Time <i>Tiempo de Secado</i> @ 70% RH | 58°F+ |
| | Touch: 30 min. <i>Tacto: 30 minutos</i> |
| Dry Time: 1 hour <i>Tiempo de Secado: 1 hora</i> | |
| Temperature and humidity dependent <i>Dependiente de temperatura y humedad</i> | |

SURFACE PREPARATION: Follow standard practices and procedures for properly preparing surfaces for the application of water base acrylic paints. Surfaces must be free of dirt, oil and grease. Remove all loose, flaking or chalking surfaces. Prime surfaces using a 100% acrylic primer (we recommend Zinsser's Bulls Eye 1-2-3® for exterior use and Zinsser's Bulls Eye® WATERBASE for interior use) and allow primer to completely dry.

APPLICATION METHODS: *Theme Paint* is specifically formulated for a wide variety of application techniques employed by professional scenic artists and decorative painters. This gives the ability to create a variety of looks from subtle color washes for rockwork to bold saturated colors for signage. Brush, roll or spray apply onto any properly prepared interior or exterior surface, thinning with water as necessary. It is perfect for color retentive washes and over glazes. Do not apply in temperatures below 58°F/14°C or if relative humidity is above 80%.

TINTING: All *Theme Paint 10000 Series* colors can be intermixed to create custom colors. Do not use universal colorants to tint or shade product unless color fading is acceptable.

PROTECTIVE CLEAR COATING: In certain exterior applications where additional weathering protection is desired, use *Theme Paint Exterior Dead Flat Varnish*, a UV protective clear topcoat, to protect your painted project. This 100% acrylic, water base, protective clear top coat is formulated

with maximum levels of UV Blockers and UV Inhibitors to further reduce the effects of harmful ultraviolet rays.

CLEAN UP: Clean brushes, rollers, tools and equipment with warm, soapy water immediately after use.

HANDLING & STORAGE: To avoid skinning, close container after each use. Keep lid tightly closed during storage. Protect from freezing. If contents freeze, allow thawing at room temperature before use. Dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

HEALTH & SAFETY: Avoid contact with eyes. Wash hands after use. Do not take internally. When spraying or sanding wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

KEEP OUT OF REACH OF CHILDREN

WARRANTY: This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Visit modernmasters.com for Technical Data Sheets, Material Safety Data Sheets, Application Instructions and the latest information on all our specialty water base paints and coatings.

To view instructional videos, visit Modern Masters YouTube Channel

MAX. VOC 50 g/L

Modern Masters
Valencia, CA 91355 USA
(800) 942-3166
modernmasters.com

© 2015, Modern Masters Inc.
Made in USA