



**Wildfire**  
LIGHTING & VISUAL EFFECTS  
Ignite Your Imagination™

**Sheen Leveler**  
Polyurethane Top Coat

• Water Base • Non-Yellowing • Satin Sheen

**SPECIFICALLY FORMULATED**  
FOR MAXIMUM BRIGHTNESS UNDER BLACKLIGHT

32 fl. oz. / 946 ml

## WILDFIRE FLUORESCENT PRODUCTS

Originally developed for the scenic studios in Hollywood to create dramatic visual effects for film, television, theme parks and other "high profile" amusement venues,

Wildfire brand fluorescent products are the standard for the visual effects professional.

Modern Masters' latest breakthrough in fluorescent coatings technology is Wildfire

Invisible Clear Color, a unique addition to the Wildfire family of brilliant, color balanced, UV-activated paints. Invisible Clear Color, when applied under normal lighting conditions, over any previously painted surface, appears to be a typical, low sheen, protective clear top coat. But, when UV blacklight is applied Wildfire Invisible Clear Color comes to life with the maximum color brilliance you've come to expect from Wildfire!



**Where to Use** For use over invisible clear colors only. Images created with Invisible Clear Colors may still be detected in visible light due to variations in the sheen. For example, a stenciled image over a dead flat surface. To eliminate the visible variation in sheen apply "Sheen Leveler" over the painted image and the surrounding area.

**Surface Preparation** Allow your project to dry for 24 to 48 hours before applying Sheen Leveler. Painted surface should be clean, dry and fully cured prior to application. Apply on a small test area to ensure desired effect is achieved.

**Application Methods** Product is ready to use, do not dilute with water. For best results apply with an airbrush, HVLP spray equipment, artist brushes or varnish roller. Apply one or two coats of Sheen Leveler over the entire completed project for total invisibility. Do not apply when air and surface temperatures are below 50 F (10 C) or high humidity conditions exist. Optimal conditions are 60 F (16 C) to 80 F (27 C) and 30% to 60% relative humidity. Stir thoroughly before use, do not shake.

**Coverage** Sheen Leveler covers approx. 75-100 sq. ft / quart, 6.75-9.0 M<sup>2</sup> / 946ml.  
**Dry Times** Dry-to-touch is approximately 30 minutes, re-coat time is approximately 2 hours. The dry time will vary with temperature and humidity.

**Cleanup** Clean tools, brushes and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.  
**V.O.C.** Contains less than 150 grams/liter.

**Handling & Storage** Store Sheen Leveler out of direct sunlight. To avoid skinning, close container after each use. Keep lid tightly closed during storage. Protect from freezing.

**Health & Safety** Ensure fresh air entry during application and drying. Avoid contact with eyes, skin and clothing. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted (NIOSH approved) respirator. Follow respirator manufacturer's directions for respirator use. Wash thoroughly after handling. Refer to product MSDS for additional health and safety information.

**First Aid** In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN**  
**CONFORMS TO ASTM D4236**

Modern Masters Inc. • Valencia, CA 91355 USA  
modernmasters.com • (800) 942-3166 • Made in USA

Wildfire® and its symbol are registered trademarks of Wildfire Lighting & Visual Effects Torrance, CA www.wildfirefx.com