



Technical Data Sheet

Modern Masters Inc. (800) 942-3166
28358 Constellation Road Suite 600 Valencia, CA 91355

Colorfast EX ZERO VOC Accelerator CFEXA10601

COLORFAST EX ACCELERATOR IS AN ORGANIC TIN CATALYST WHICH HELPS THE SPEED OF DRY OF MODERN MASTERS' COLORFAST ACRYLIC/POLYURETHANE TWO-COMPONENT TOPCOATS. WHEN USED AS DIRECTED, IT ALLOWS PAINTED SURFACES TO BE BACK IN SERVICE WITHIN HOURS.

Characteristics:

Weight per Gallon (lbs)	11.15
Specific Gravity	1.339
Coating VOC (g/L)	0
Coating VOC (lbs/gal)	0
Material VOC (g/L)	0
Material VOC (lbs/gal)	0
Flash Point (TCC)	109°F
VOC Partial Vapor Pressure (mmHg) @ 20°F	0.0

Recommended Addition Levels:

Typically, 1-2 ounces/ mixed gallon range is most effective. It is not recommended to add over 3 ounces per mixed gallon. Sagging and running may occur.

The chart below approximates the addition levels of Accelerator to obtain a 3-4 hour tape time and maintain a 60-90 minute pot life. This will vary slightly depending on color and gloss of formulation.

Temperature Range	Amount Added ounces
55°F-62°F	2.5 to 3
63°F -70°F	2
71°F -78°F	1.5
79°F -86°F	1
87°F -94°F	0.5
95+°F	add as only as needed

Shelf Life: 24 month shelf life requirement for this product is specified.

For SDS and Technical Data Sheets for products mentioned in this go to www.modernmasters.com or contact your Modern Masters technical representative.