Technical Data Sheet

Modern Masters Inc. (800) 942-3166
9380 San Fernando Rd., Sun Valley CA 91352 An RPM Company

Decorative Painter's Tintable Glaze (Scumble)

Water Base, 100% Acrylic, Non-Yellowing
For Professional Use
Perfect for Creating All Faux Finishes

DP608

Modern Masters Tintable Glaze is a professional grade, 100% acrylic, non-yellowing, water base, clear medium. Perfect for creating faux finishes (marbling, wood graining, exotic mineral, etc.) on furniture, cabinetry, decorative moldings and other nonporous surfaces.

Surface Preparation –Tintable Glaze should be applied over a previously painted and fully cured, 100% acrylic semi-gloss latex surface. The surface should be clean and sound. **Note: Not intended for use over oil base finishes.**

Application – The thicker *Tintable Glaze* is applied, the longer it will stay "open" and workable. Generally the glaze will stay "open" for one hour, depending on color concentration, film thickness and humidity. The cooler and more humid the air, the longer the glaze will stay wet. When working in hot, dry climates or when more "open" time is desired, add Modern Masters ***Extender for Latex Paint*** to the *Tintable Glaze.*

Protection – Do not clean an unprotected glazed surface with harsh chemicals. Surfaces that will be handled should be protected with two coats of Modern Masters **Dead Flat** or **Satin Varnish** for interior surfaces. All exterior surfaces should be protected with **Exterior Dead Flat Varnish**. Follow the instructions on the container label.

Dry Times – The colored glaze will dry to an eggshell sheen in approximately 3 hours and fully cure in 36 hours.

Coverage – Approximately 150 to 200 square feet per qt., 13.9-18.5m²/946 ml.

Clean Up – Clean tools, brushes and equipment with warm, soapy water immediately after use. Promptly wipe up spills and splatters with a damp cloth.

Material VOC – Contains less than 875 g/l. This product can only be sold or used as part of a Faux Finishing coating system.

Handling & Storage – When not in use, close container tightly and store at room temperature. Protect product from freezing and from extreme heat. Do not reuse this container and dispose of empty container properly.

Health & Safety –Use in a well-ventilated area. Avoid contact with eyes. Wash hands thoroughly after use. Do not take internally. When spraying or sanding, use a properly-fitting, NIOSH approved respirator per the manufacturer's instructions.

Skin contact: Thoroughly wash with soap and warm water before the coating dries. Individuals with sensitive skin may require gloves.

Eye contact: Rinse with clean water for 15 minutes. Seek medical attention.

Inhalation: To help prevent irritation, use only in well-ventilated areas. If irritation occurs, move to fresh air. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

Read the Material Safety Data Sheet for Additional Health and Safety Information.

Warranty – This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques, and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used, if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

Technical Assistance – For additional technical assistance contact our Technical Department at 818-683-0201 or e-mail technical@modernmasters.com.

Disclaimer: Modern Masters, Inc. believes, to the best of its knowledge, information, and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained

Container Size	Container Weight Under
1 Quart	2.5 lbs.